

# Port-A-Cool Cyclone™ 3000



**Centrifugal Air Supply,  
1/3 h.p. Two-Speed Motor  
Cools 700 sq. ft.**

- Adjustable Louvers
- Quieter Running Centrifugal Fan
- Smaller Footprint

- Lowers temperatures up to 30 degrees F
- Energy efficient 5.6 amps for pump and motor
- Water level sight tube and sump drain
- 3/4" garden hose connection for longer running
- Durable one-piece, rust-free, leak-proof molded polyethylene housing
- Environmentally friendly efficient and effective resource use
- Cools for a fraction of the cost of air conditioning
- Cools without chemicals or refrigerants
- Long-term dependability—near maintenance-free operation
- Shipped completely assembled— ready to operate out of the box
- UL Listed (electric models) in U.S. and Canada

## Port-A-Cool Cyclone™ 3000 Specifications

|                  |                    |
|------------------|--------------------|
| Speeds           | Two                |
| Air Delivery CFM | 2,400 / 3,000      |
| Total Amps       | 5.6                |
| Water reservoir  | 16 gallons         |
| Dimensions       | 38"h x 29"w x 25"d |
| Unit weight      | 100 lbs.           |
| Shipping weight  | 113 lbs.           |
| Box Size         | 42"h x 31"w x 27"d |
| Cooling Capacity | 700 sq. ft.        |

**STOCK NUMBER PAC2KCYC01 (BLACK)**  
**STOCK NUMBER PAC2KCYC01A (SIENNA)**